

Pneumatic Equipment


F.R.L. Combination (AAC ABC Series)



Ordering Code

AAC	1500	M
Model	Port size	Drain type
AAC : Mini series F.R.L. unit	1500 : 1/8" 2000 : 1/4"	Blank : semi-auto drain M : Manual drain A : Auto drain
ABC : Medium series F.R.L. unit	3000 : 3/8" 4000 : 1/2"	

Symbol



Specifications

Model No		AAC1500	AAC2000	ABC2000	ABC3000	ABC4000
Port size		1/8	1/4	1/4	3/8	1/2
Media		Air				
Pressure range	kgf/cm ²	0.50 ~ 8.50				
Maximum pressure	kgf/cm ²	9.50				
Fluid temperature	°C°F	+5 ~ +60 (+41 ~ +140)				
Recommendable lubricant		ISO VG32 or Equivalent				
Drain bowl capacity	CC.	15	15	60	60	60
Oil bowl capacity	CC.	25	25	90	90	90
Weight	g	700	700	900	900	900
Autodrain model		ADK6268				


F.R.L. Combination (AAFC ABFC Series)



Ordering Code

AAFC	2000	M
Model	Port size	Drain type
AAFC : Mini series FR.L. unit	1500 : 1/8" 2000 : 1/4"	Blank : semi-auto drain M : Manual drain A : Auto drain
ABFC : Medium series FR.L. unit	3000 : 3/8" 4000 : 1/2"	

Symbol



New (NAFC Series)



Specifications

Model No		AAFC1500	NAFC1500	AAFC2000	NAFC2000	ABFC2000	ABFC3000	ABFC4000
Port size		1/8	1/8	1/4	1/4	1/4	3/8	1/2
Media		Air						
Pressure range	kgf/cm ²	0.50 ~ 8.50						
Maximum pressure	kgf/cm ²	9.50						
Fluid temperature	°C°F	+5 ~ +60 (+41 ~ +140)						
Recommendable lubricant		ISO VG32 or Equivalent						
Drain bowl capacity	CC.	15	15	15	15	60	60	60
Oil bowl capacity	CC.	25	25	25	25	90	90	90
Weight	g	500	500	500	500	700	700	700
Autodrain model		ADK6268						


F.R.L. Combination (AAFR ABFR Series)



Ordering Code

AAFR	2000	M
Model	Port size	Drain type
AAFR : Mini series Filter/Regulator unit	1500 : 1/8" 2000 : 1/4"	Blank : semi-auto drain M : Manual drain A : Auto drain
ABFR : Medium series Filter/Regulator unit	3000 : 3/8" 4000 : 1/2"	

Symbol



New (NAFR Series)



Specifications

Model No		AAFR1500	NAFR1500	AAFR2000	NAFR2000	ABFR2000	ABFR3000	ABFR4000
Port size		1/8	1/8	1/4	1/4	1/4	3/8	1/2
Fluid		Air						
Pressure range	kgf/cm ²	0.50 ~ 8.50						
Maximum pressure	kgf/cm ²	9.50						
Fluid temperature	°C°F	+5 ~ +60 (+41 ~ +140)						
Drain bowl capacity	CC.	15	15	15	15	60	60	60
Weight	g	260	260	260	260	400	400	400
Autodrain model		ADK6268						