


Pneumatic Equipment

Solenoid Valve (A2PAV Series)




Ordering Code




Specifications

Model NQ		A2PAV-10	A2PAV-15	A2PAV-20	A2PAV-25	A2PAV-32	A2PAV-40	A2PAV-50
Port size	inch	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Medium		Air, Oil, Water, natural gas, liquid, steam						
Pressure	kgf/cm ²	3~10						
Material of body		Stainless Steel						

Solenoid Valve (A2HPW Series)



Ordering Code




Specifications

Model NQ		A2HPW160-15	A2HPW160-20	A2HPW160-25
Port size	inch	1/2	3/4	1
Fluid		Air, Oil, Water		
Action type		Direct acting normally closed		
Air operation pressure	kgf/cm ²	0~50		
Oil operation pressure	kgf/cm ²	0~50		
Water operation pressure	kgf/cm ²	0~50		
Fluid temperature	°C	-5~+150		
Voltage		AC110V:AC110V 50/60Hz, AC220V:AC220V 50/60Hz, DC24V:DC24V		
Voltage range	%	±10		
Material of body		Brass		

Solenoid & Pilot Actuated Poppet Valve (A3PV A3PA Series)



Ordering Code



Specifications

Model NQ		A3PV150-15	A3PV200-20	A3PV250-25	A3PV380-40
		A3PA150-15	A3PA200-20	A3PA250-25	A3PA380-40
Port size	inch	1/2	3/4	1	1 1/2
Pilot port size	inch	1/8	1/8	1/8	1/8
Flow rate	I/min	4800	6100	12000	33500
Maximum pressure	Kgf/cm ²	2.5 ~ 10			
Fluid temperature	°C	-5 ~ 70			
Valve type		3/2 way pilot & single solenoid			
Action type		Normally closed, normally open			
Material of body		Nickel plated Brass			