

CONTACT NO: CAVITE LINE (046)419-8440
(046)686-2217
(046)686-2204
MANILA LINE (028)463-1269
(028)463-1270
(028)463-1279

EMAIL: airtac.atcgroup@yahoo.com
ADDRESS: Unit 57 & 58 Century Complex V
Salawag Dasmariñas, Cavite



ATC
VALVE



Multi-standard wafer butterfly valve

Lug type wafer butterfly valve

Double flange butterfly valve

防結露蝶閥
Anti-knot dew butterfly valve



Grooved butterfly valves

Three eccentric metal seals wafer butterfly valve

Three eccentric metal hard seal flange butterfly valve

Wafer lined fluorine butterfly valve



Double flange lined fluorine butterfly valve

GB soft-seal gate valve

DIN soft-seal gate valve(F4)

DIN soft-seal gate valve(F5)



DIN Cast iron hard seal gate valve F4

DIN Cast iron hard seal gate valve F5

JIS Cast iron gate valve

BS Soft sealing gate valve



ANSI hard sealing gate valve

ANSI soft sealing gate valve 200PSI

ANSI soft sealing gate valve 300PSI

ANSI Cast steel/stainless steel gate valves



DIN Cast steel/stainless steel gate valve F4

DIN Cast steel/stainless steel gate valve F5

JIS Cast steel/stainless steel gate valve 10K

Forged steel flange gate valve



Forged steel threaded /weld gate valve

Manual lug/flanged knife gate valve

Pneumatic knife gate valve

Electric knife gate valve



DIN Cast iron ball valve

JIS Cast iron ball valve

ANSI Cast iron ball valve

ANSI Cast steel/stainless steel ball valves



2PC Trunnion mounted ball valve

3PC Trunnion mounted forged steel ball valve

JIS Cast steel ball valve 10K

DIN Cast iron globe valve



ANSI Cast iron globe valve

JIS Cast iron globe valve 10K

ANSI Cast steel/stainless steel globe valves

DIN Cast steel/stainless steel globe valves



JIS Cast steel/stainless steel globe valves



Forged steel flange globe valve



Forged thread /weld globe valve



DIN Cast iron swing check valve



ANSI Cast iron swing check valve



BS Cast iron swing check valve



JIS Cast iron swing check valve 10K



Ball check valve



Rubber disc check valve



Wafer type check valve



ANSI Cast steel / stainless steel swing check valve



JIS Cast steel / stainless steel swing check valve



JIS Cast steel / stainless steel swing check valve



Forged steel flange swing check valve



Forged steel thread /welded swing check valve



Foot Valve



Foot Valve



1PC Threaded ball valve



2PC Threaded ball valve



3PC Threaded ball valve



Threaded gate valve



Thread globe valve



Thread check valve



Thread strainer



DIN Cast iron strainer



ANSI Cast iron strainer



JIS Cast iron strainer



ANSI Cast steel/stainless steel strainer



JIS Cast steel/stainless steel strainer



Single flange/thread bleed valve



Double ball air valve, combined air vent valve



100X Remote control float valve



Electric remote float valve



200X pressure reducing valve



300X slow closing reverse valve



400X Flow control valve



500X Pressure relief/pressure valve



600X hydraulic electric control valve



700X pump control valve



800X Pressure differential bypass balancing valve



900X emergency shut-in valve



745X piston type multi-function pump control valve

PRODUCT DISPLAY



High Temperature Control Valve
Size : DN25-400
Pressure : PN16-64
Material : WCB/CF8/CF3M

Balance Cage Type Control Valve
Size : DN32-400
Pressure : PN16-64
Material : WCB/CF8/CF3M



Single Seat Control Valve
Size : DN15-200
Pressure : PN16-64
Material : WCB/CF8/CF3M



Multi-stage Decompression Type Control Valve
Size : DN25-400
Pressure : PN16-64
Material : WCB/CF8/CF3M



Antibiotics Control Valve
Size : DN25-300
Pressure : PN16-64
Material : WCB/CF8/CF3M



Angle Type Control Valve
Size : DN25-200
Pressure : PN16-64
Material : WCB/CF8/CF3M



Hydraulic Control Valve
Size : DN25-300
Pressure : PN16-64
Material : WCB/CF8/CF3M



Electric Fluorine lined Control Valve
Size : DN25-300
Pressure : PN10-25
Material : WCB+F46/F4/PFA
304+F46/F4/PFA





Carbon Steel Pipe Fittings



WESDOM GROUP

Flange



Multi-Function Pipe Repair & Coupling



Joint



Cast Iron Pipe Fittings



Groove Pipe Fitting



Rigid Coupling



Flexible Coupling



Mechanical Tee Grooved outlet



Mechanical Tee Threaded outlet



Grooved flange



90° Elbow



45° Elbow



22.5° Elbow



11.25° Elbow



Tee



Grooved Reducing Tee



Threaded Reducing Tee



Cross



Grooved Reducing Cross



Threaded Reducing Cross



Cap



Grooved Concentric Reducer



Threaded Concentric Reducer



Grooved Eccentric Reducer



Adaptor Flange

Fire Control Series



Alarm Valve

> Wet Alarm Check Valve Groove Type



> Deluge Alarm Valve Groove Type



> Deluge Alarm Valve



Technical Parameters

Size	DN100	DN150	DN200	DN250
Working Pressure	1.2MPa			
Sealing Testing	2.4MPa			
Strength Testing	4.8MPa			
Control Way	Electronic control, guidance, manual type			



TN05-MS-01



TN05-MS-04



TN05-MS-07



TN05-MS-08



TN05-MS-02



TN05-MS-05



TN05-MS-07



TN05-MS-03



TN05-MS-06

Code Number	Specification
TN05-MS-01	Φ 165 - 2.5" BS336
TN05-MS-02	BSPT2.5" - 2.5" BS336
TN05-MS-03	BSPT2.5" - 2.5" BS336
TN05-MS-04	4" x 2 Way (2.5" BS336) Breeching



Canvas Fire Hose

- Lining: Natural rubber or PU
- Working pressure: 8, 10, 13, 16bar
- Size: 1"-4"
- Color: white, red, yellow
- Length: 0-30M

PVC Layflat Hose

- Working pressure: 2-8 Bar
- Size: 1"-8"
- Color: Blue, red
- Length: 0-100M

GB14561-2003



TN11-A-03