



专业的制冰设备制造商
Professional commercial&industrial ice system provider



专注制冰二十余年
Extensive industry experience

制冷行业领导品牌
Refrigeration industry leader

一站式解决方案
One-stop solution





小型商业片冰机

Commercial flake ice machine



技术参数 TECHNICAL DATA

- ◆ 标准工况:环境温度25℃,水温.20℃
- ◆ The technical data based on 25℃ ambient temp.
- ◆ 蒸发温度 The evaporating temperature:-20℃
- ◆ 冷凝温度 The condensing temperature:40℃
- ◆ 电源要求 Power supply:3P/380V/50Hz
- ◆ 冰片厚度 The ice thickness:1.6-2.3mm
- ◆ 制冷剂 Refrigerant:R404A

型 号	Model	MIF0.35T-R4A	MIF0.6T-R4A	MIF1T-R4A	MIF1.2T-R4A
日产量 (T/24H)	Daily Output (Ton/24hrs)	0.35t	0.6t	1t	1.2t
制冷量 (kw)	Cooling Capacity(kw)	2	3.3	5.6	6.6
输入总功率 (kw)	General Power(kw)	1.95	4.76	4.04	4.72
压缩机输入功率 (kw)	Compressor Input(kw)	1.59	2.27	3.86	4.81
减缩机输入功率 (kw)	Reductor Power(kw)	0.25	0.18	0.18	0.18
冷却方式 (风冷)	Cooling Mode	Air cooling	Air cooling	Air cooling	Air cooling
进水/排水管径	Water Inlet/Drain Pipe	1/2"	1/2"	1/2"	1/2"
重量 (KG)	Weight(kg)	190KG	300KG	450KG	460KG
机组尺寸 (mm)	Dimension(mm)	950*650*700	1050*700*800	1320*900*900	1320*900*900
带冰库尺寸 (mm)	Dimension(with ice bin)	950*800*1530	1280*1100*1850	1320*1185*2100	1320*1185*2100

型 号 Model	Model	MIF1.6T-R4A	MIF2T-R4A	MIF2.5T-R4A	MIF3T-R4A
日产量 (T/24H)	Daily Output(Ton/24hrs)	1.6t	2t	2.5t	3t
制冷量 (kw)	Cooling Capacity(kw)	9.8	11.6	15.5	17.2
输入总功率 (kw)	General Power(kw)	9.18	10.37	13.37	14.03
压缩机输入功率 (kw)	Compressor Input(kw)	9	10	13	13.66
减缩机输入功率 (kw)	Reductor Power(kw)	0.18	0.37	0.37	0.37
冷却方式 (风冷)	Cooling Mode	Air cooling	Air cooling	Air cooling	Air cooling
进水/排水管径	Water Inlet/Drain Pipe	1/2"	1/2"	1/2"	1/2"
重量 (KG)	Weight(kg)	480KG	500KG	550KG	600KG
机组尺寸 (mm)	Dimension(mm)	1500*1100*1000	1500*1100*1100	1700*1200*1100	1700*1200*1320
带冰库尺寸 (mm)	Dimension(with ice bin)	1500*1420*2300	1500*1420*2400	1700*1520*2600	1700*1520*2850

任何一款机器都可以选择风冷或水冷。Both air-cooling and water cooling for each mode for your option.
任何一款机器都可以根据客户要求的电制生产。All ice machines can be produced according to the power supply which customers request.



大型工业片冰机

Industry flake ice machine

技术参数 TECHNICAL DATA

- ◆ 标准工况:环境温度25℃,水温.20℃
- ◆ The technical data based on 25C ambient temp.
- ◆ 蒸发温度 The evaporating temperature:-20℃
- ◆ 冷凝温度 The condensing temperature:38℃
- ◆ 电源要求 Power supply:3P/380V/50H
- ◆ 冰片厚度 The ice thickness:1.6~2.3mm
- ◆ 制冷剂 Refrigerant:R22/R404A



型 号	Model	MIF5T-R2W	MIF8T-R2W	MIF10T-R2W	MIF15T-R2W
日产量 (T/24H)	Daily Output(Ton/24hrs)	5t/24h	8t/24h	10t/24h	15t/24h
制冷量 (kw)	Cooling Capacity(kw)	38.7	54.1	76.5	101.5
输入总功率 (kw)	General Power(kw)	22.55	33	45.5	54
压缩机输入功率 (kw)	Compressor Input(kw)	20.5	27.1	40.7	45.6
减速机输入功率 (kw)	Reductor Power(kw)	0.37	0.75	0.75	0.75
冷却方式 (水冷)	Cooling Mode	Water cooling	Water cooling	Water cooling	Water cooling
冷却塔流量 (m³/h)	Cooling Tower (m³/h)	20	30	45	60
进水/排水管径	Water Inlet/Drain Pipe	3/4" ; 1/2"	3/4";1/2"	3/4";1/2"	2*3/4";1/2"
重量 (KG)	Weight(kg)	980KG	1670KG	2020KG	3850KG
整机尺寸 (mm)	Dimension(mm)	2030*1500*1470	2200*1890*1650	2200*1900*1750	3500*2100*2100

型 号	Model	MIF20T-R2W	MIF25T-R2W	MIF30T-R2W	MIF40T-R2W
日产量 (T/24H)	Daily Output(Ton/24hrs)	20t/24h	25t/24h	30t/24h	40t/24h
制冷量 (kw)	Cooling Capacity(kw)	131.4	164.5	181	240
输入总功率 (kw)	General Power(kw)	64.5	81	90.1	120
压缩机输入功率 (kw)	Compressor Input(kw)	55.9	70.6	78.6	96
减速机输入功率 (kw)	Reductor Power(kw)	0.75	0.75	1.5	1.5
冷却方式 (水冷)	Cooling Mode	Water cooling	Water cooling	Water cooling	Water cooling
冷却塔流量 (m³/h)	Cooling Tower (m³/h)	70	78	95	95
水/排水管径	Water Inlet/Drain Pipe	2*3/4";1/2"	2*3/4";1/2"	2*3/4";1/2"	2*3/4";1/2"
重量 (KG)	Weight(kg)	4100KG	4250KG	4500KG	5400KG
整机尺寸 (mm)	Dimension(mm)	3500*2100*2200	3600*2100*2450	4000*2100*2620	4200*2100*3100

任何一款机器都可以选择风冷或水冷。Both air-cooling and water cooling for each mode for your option.

任何一款机器都可以根据客户要求的电制生产。All ice machines can be produced according to the power supply which customers request.

管冰机

Tube ice machine



技术规格 TECHNICAL DATA

- ◆ 标准设计工况:环境温度30℃,进水温度20℃
- ◆ 试用工况:环境温度5℃-40℃,水温5℃-40℃
- ◆ 客户可选管冰规格: $\varnothing$ 22、 $\varnothing$ 29、 $\varnothing$ 35、 $\varnothing$ 42
- ◆ 客户可选择制冷剂: R22/R404A/R717
- ◆ Refrigerant: R22/R404A/R717
- ◆ The evaporating temp. /condensing temp: -15 C/40℃
- ◆ Ice tube external diameter: $\varnothing$ 22、 $\varnothing$ 29、 $\varnothing$ 35、 $\varnothing$ 42
- ◆ Standard ambient/water temp: 30℃/20℃

型号	Model	MIT1T-R4A	MIT2T-R4A	MIT3T-R4A	MIT5T-R4A
标准制冰量	Ice Output	1t/24h	2t/24h	3t/24h	5t/24h
制冷量 (kw)	Cooling Capacity	11.9	18.8	33.5	49.6
输入总功率 (kw)	Input Power	6.21	8.39	14.5	22.73
重量 (kg)	Ice Machine Wight	950	1150	1280	1600
机组尺寸 (mm)	Ice Machine Diameter	1440*900*1950	1650*1300*2150	1650**1300*2150	1750*1400*2200
分体冷凝器尺寸	Dimension Of Remote Condenser (outdoor)	1100*450*870	1100*500*870	2000*650*1145	2000*700*1145

型号	Model	MIT5T-R2W	MIT10T-R2W	MIT20T-R2W	MIT30T-R2W
标准制冰量	Ice Output	5t/24h	10t/24h	20t/24h	30t/24h
制冰量 (kw)	Cooling Capacity	50.7	80.9	161.8	242.7
输入总功率 (kw)	Input Power	23.8	42.85	82	115.7
重量 (kg)	Ice Machine Weight	1600	2750	5200	6400
机组尺寸 (mm)	Ice Machine Diameter	1750*1400*2200	2300*1600*3100	2400*2100*2250	2900*2100*2250
室外冷却塔尺寸 (mm)	Dimension Of Cooling Tower	Φ 1385*2150	Φ 1880*2120	Φ 2900*2690	Φ 2900*2875
冷却塔运行重量 (kg)	Weight Of Cooling Tower	500	975	1600	1680

任何一款机器都可以选择风冷或水冷。Both air-cooling and water cooling for each mode for your option.
任何一款机器都可以根据客户要求的电制生产。All ice machines can be produced according to the power supply which customers request.

片冰机蒸发器

Ice flaker evaporator

技术参数 TECHNICAL DATA

- ◆ 标准工况:环境温度25℃,水温.20℃
- ◆ The technical data based on 25℃ ambient temp.
- ◆ 蒸发温度 The evaporating temperature:-20℃
- ◆ 冷凝温度 The condensing temperature:38℃
- ◆ 电源要求 Power supply:3P/380V/50Hz
- ◆ 冰片厚度 The ice thickness:1.6~2.3mm
- ◆ 制冷剂 Refrigerant:R22/R404A



型号Model	Model	MIF-1T	MIF-1.5T	MIF-2T	MIF-2.5T	MIF-3T	MIF-5T
日产量 (Ton/24hrs)	Daily Output(Ton/24hrs)	1t	1.5t	2t	2.5t	3t	5t
必要制冷量 (kw)	Necessary Refriger(kw)	6kw	9.8kw	12kw	15.5kw	18kw	30kw
额定电压	Voltage	380V/50Hz/3P			380V/50Hz/3P		
减速机功率 (kw)	Reductor Power(kw)	0.18kw	0.18kw	0.37kw	0.37kw	0.37kw	0.37kw
进水排水管径	Water Inlet/Drain Pipe	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
机组尺寸 (mm)	Dimension(mm)	790*580*900	790*580*1000	900*680*1050	950*680*1100	950*680*1200	1180*1050*1420
重量 (KG)	Weight(kg)	160	200	240	260	280	370

型号Model	Model	MIF-10T	MIF-15T	MIF-20T	MIF-25T	MIF-30T	MIF-40T
日产量 (Ton/24hrs)	Daily Output(Ton/24hrs)	10t	15t	20t	25t	30t	40t
必要制冷量 (kw)	Necessary Refriger(kw)	60kw	90kw	120kw	150kW	180kw	240kw
额定电压	Voltage	380V/50Hz/3P			380V/50Hz/3P		
减速机功率 (kw)	Reductor Power(kw)	0.55kW	0.75kW	0.75kW	0.75kW	1.5kW	1.5kW
进水排水管径	Water Inlet/Drain Pipe	3/4" 1/2"	3/4" 1/2"	3/4" 1/2"	3/4" 1/2"	3/4" 1/2"	3/4" 1/2"
机组尺寸 (mm)	Dimension(mm)	1580*1500*1670	1580*1500*2130	2130*1850*2240	2130*1850*2550	2520*2250*2500	2550*2250*3000
重量 (KG)	Weight(kg)	1100	1550	2200	2500	3000	3500

海水片冰机

Seawater flake ice machine

技术参数 TECHNICAL DATA

- ◆ 标准工况:环境温度25℃,水温.20℃
- ◆ The technical data based on 25℃ ambient temp.
- ◆ 蒸发温度 The evaporating temperature:-30℃
- ◆ 冷凝温度 The condensing temperature:38℃
- ◆ 电源要求 Power supply:3P/380V/50Hz
- ◆ 冰片厚度 The ice thickness:1.6~2.3mm
- ◆ 制冷剂 Refrigerant:R404A




型 号	Model	MIF1T-R4SW	MIF2T-R4SW	MIF3T-R4SW	MIF5T-R4SW
日产量 (T/24H)	Daily Output(Ton/24hrs)	1t/24h	2t/24h	3t/24h	5t/24h
制冷量 (kw)	Cooling Capacity(kw)	6.7kw	12.2kw	19kw	31.6kw
输入总功率 (kw)	General Power(kw)	5.25kw	8.91kw	12.24kw	22.39kw
压缩机输入功率 (kw)	Compressor Input(kw)	4.38kw	7.67kw	11kw	20.4kw
减速机功率 (kw)	Reductor Power(kw)	0.37kw	0.37kw	0.37kw	0.37kw
冷却方式	Cooling Mode	Seawater cooling	Seawater cooling	Seawater cooling	Seawater cooling
进水排水管径	Water Inlet/Drain Pipe	1/2"	1/2"	1/2"	3/4"
重量 (KG)	Weight(kg)	500KG	600KG	650KG	1050KG
机组尺寸 (mm)	Dimension(mm)	1320*950*1000	1500*1200*1300	1500*1200*1350	1800*1500*1560

任何一款机器都可以选择风冷或水冷。Both air-cooling and water cooling for each mode for your option.
任何一款机器都可以根据客户要求的电制生产。All ice machines can be produced according to the power supply which customers request.

条冰机

Block ice machine



直冷式条冰机 Direct cooling block ice machine

Model	Capacity	Refrigerant	Total power	Dimension	
	Ton/D		Kw	Part name	(L*W*H)mm
MIB-10	1T	R22/R404A	6.0	Complete unit	1800*1200*2000
MIB-20	2T	R22/R404A	10.0	Complete unit	2800*1400*2000
MIB-30	3T	R22/R404A	14.0	Complete unit	3600*1400*2200
MIB-50	5T	R22/R404A	25.0	Refrigeration unit	1400*1000*1250
				Evaporator	4800*1000*2250
MIB-100	10T	R22/R404A	50.0	Refrigeration unit	1800*1000*1450
				Evaporator	4800*1000*2250
MIB-150	15T	R22/R404A	75.0	Refrigeration unit	2000*1200*1600
				Evaporator	4800*1000*2250
MIB-200	20T	R22/R404A	105.0	Refrigeration unit	2400*1600*1800
				Evaporator	4800*1000*2250

自动送冰系统

Automatic ice delivery system



型号 Model	MTS-10	MTS-15	MTS-20	MTS-25
送冰量(吨/小时) Delivery capacity (ton/hour)	10	15	20	25
输送管径 (mm) Diameter of screw tube	250	300	300	350

任何一款机器都可以选择风冷或水冷。Both air-cooling and water cooling for each mode for your option.
任何一款机器都可以根据客户要求的电制生产。All ice machines can be produced according to the power supply which customers request.